



The University of
Nottingham

UNITED KINGDOM • CHINA • MALAYSIA

Ma, Xiaoli (2004) Investigation of novel thermoelectric refrigeration systems. PhD thesis, University of Nottingham.

Access from the University of Nottingham repository:

http://eprints.nottingham.ac.uk/12377/3/program_B.pdf

Copyright and reuse:

The Nottingham ePrints service makes this work by researchers of the University of Nottingham available open access under the following conditions.

This article is made available under the University of Nottingham End User licence and may be reused according to the conditions of the licence. For more details see:
http://eprints.nottingham.ac.uk/end_user_agreement.pdf

For more information, please contact eprints@nottingham.ac.uk

```

// the fin design for the cranked heat pipe.
// the overall heat transfer, total thermal resistance, the total
// fin efficiency and the fin effectiveness are required to calculate.

#include <iostream.h>
#include <math.h>

double W,L,t1,t,P1,P,Ao,Af,qt,At;
// W is length of fin and also the length of flat panel;L is the height
// of fin, t is the thickness of fin, t1 is the thickness of the flat
panel.
// P1 is the width of flat panel.P is the perimeter of the fin;Ao is the
exposure
// area; Af is the surface area of a single fin;At is the total area; qt
is the
//total heat transfer;
double h,A; //h is the convection coefficient; A is the
//cross-sectional area;
double Rw,Aw,Rfins,Rtotal; //Rw is the thermal resistance of wall; Aw is
the area of wall;
//Rfins is the thermal resistance of fins;Rtotal is
total resistance;
double Ti,T8,T0,k,kw;
//Ti is temperature of internal side of flat panel; T8 is temperature of
ambient;
// T0 is temperature of base wall surface;
//k is the thermal conductivity of fin material aluminum, kw is thermal
conductivity
// of flat panel copper.
double m,Lc,yetafin,yetatotal,deltax;
//yetafin is the efficiency of a single fin;
//yetatotal is the total efficiency of fins;
//deltax is the thickness of the flat panel

double L1;
main ()
{
//cout<<"the number of fins, N="<<endl;
//cin>>N;
//cout<<"the height of fins,L="<<endl;
//cin>>L;
//cout<<"the thickness of fin,t="<<endl;
//cin>>t;
t=0.0005;
//cout<<"estimation of the convection coefficient h="<<endl;
//cin>>h;
h=19.8;
W=0.35;
P1=0.148;
t1=0.0055;
Ti=38;
T8=30;
k=236;
kw=236;
// **int N; //N is the number of fins;
//**for (N=0;N<55;N++)
int N=47;
for (L;L<0.06;L=L+0.01)

```

```

{
cout<<"h="<<h<<endl;
P=2*(W+t);
A=W*t;
m=sqrt(h*P/(k*A));
Lc=L+t/2;
yetafin=(exp(m*Lc)-exp(-m*Lc))/(exp(m*Lc)+exp(-m*Lc))/(m*Lc);
cout<<"mLc="<<m*Lc<<" " <<"L="<<L<<endl;
// cout<<"the single fin efficiency, yetafin="<<yetafin<<endl;

Aw=W*P1;
Ao=W*P1-N*(W*t);
Af=2*(W*Lc);
At=Ao+N*Af;

yetatotal=1-N*Af*(1-yetafin)/At;
// cout<<"total fin efficiency yetatotal="<<yetatotal<<endl;

Rw=t1/(kw*Aw);
Rfins=1/(yetatotal*h*At);
T0=(Ti/Rw+T8/Rfins)/(1/Rw+1/Rfins);
Rtotal=Rw+Rfins;

cout<<"yetafin="<<yetafin<<"yetatotal="<<yetatotal<<"Rtotal="<<Rtotal<<en
dl;

qt=h*At*(1-N*Af*(1-yetafin)/At)*(T0-T8);
cout<<"total heat transfer qt="<<qt<<endl;
cout<<"*****"<<endl;
}

return 0;
}

```